



Pressione max di esercizio raccomandata Kg/cm ²	Grandezza	Tipo	Dimensioni								Viti		Or tipo	Peso Kg
Maximum recommended working pressure Kg/cm ²	Size	Type	Dimensions								Screws		Or type	Weight Kg
			A	C	D	E	F	H	L	W	Metric	Unc		

SERIE 3000

345	3/4"	D100	19	47,63	71	22,23	60	19	11	G1/8 - M10x1	M10x55	3/8"x2"1/4	4100	0,42
345	3/4"	D100G1/4 *	19	47,63	71	22,23	60	25	11	G1/4 - M12x1,5	M10x60	3/8"x2"1/2	4100	0,55
345	1"	D102	25,0	52,37	71	26,19	60	19	11	G1/8 - M10x1	M10x55	3/8"x2"1/4	4131	0,35
345	1"	D102G1/4 *	25,0	52,37	71	26,19	60	26	11	G1/4 - M12x1,5	M10x60	3/8"x2"1/2	4131	0,53
276	1"1/4	D104G1/8	32	58,72	81	30,18	68	22	11,5	G1/8 - M10x1	M10x60	7/16"x2"1/2	4150	0,45
276	1"1/4	D104	32	58,72	81	30,18	70	22	11,5	G1/4 - M12x1,5	M10x60	7/16"x2"1/2	4150	0,59
207	1"1/2	D106G1/8	38	69,85	95	35,71	78	25	13,5	G1/8 - M10x1	M12x70	1/2"x2"3/4	4187	0,88
207	1"1/2	D106	38	69,85	95	35,71	78	25	13,5	G1/4 - M12x1,5	M12x70	1/2"x2"3/4	4187	0,88
207	2"	D108	51	77,77	102	42,88	90	18	13,5	G1/8 - M10x1	M12x65	1/2"x2"1/2	4225	0,78
207	2"	D108G1/4	51	77,77	112	42,88	94	24	13,5	G1/4 - M12x1,5	M12x70	1/2"x2"3/4	4225	1,16
172	2"1/2	D110	63	88,90	114	50,80	105	18	13,5	G1/8 - M10x1	M12x65	1/2"x2"1/2	4275	0,90
172	2"1/2	D110G1/4	63	88,90	114	50,80	105	25	13,5	G1/4 - M12x1,5	M12x70	1/2"x2"3/4	4275	1,26
138	3"	D112G1/8	73	106,38	134	61,93	124	23	17,5	G1/8 - M10x1	M16x75	5/8"x3"	4337	1,63
138	3"	D112	73	106,38	134	61,93	124	23	17,5	G1/4 - M12x1,5	M16x75	5/8"x3"	4337	1,63

SERIE 6000

414	1/2"	D401	13	40,49	56	18,24	48	16	9	G1/8 - M10x1	M8x45	5/16"x1"3/4	4075	0,22
414	1/2"	D401G1/4 *	13	40,49	71	18,24	60	25	9	G1/4 - M12x1,5	M8x55	5/16"x2"1/4	4075	0,60
414	3/4"	D402	19	50,80	71	23,80	60	19	11	G1/8 - M10x1	M10x60	3/8"x2"1/2	4100	0,42
414	3/4"	D402G1/4 *	19	50,80	71	23,80	60	25	11	G1/4 - M12x1,5	M10x65	3/8"x2"1/2	4100	0,55
414	1"	D403G1/8	25	57,15	81	27,76	70	22	13	G1/8 - M10x1	M12x65	7/16"x2"1/2	4131	0,63
414	1"	D403	25	57,15	81	27,76	70	22	13	G1/4 - M12x1,5	M12x65	7/16"x2"1/2	4131	0,62
414	1"1/4	D404G1/8	32	66,68	95	31,75	78	25	15	G1/8 - M10x1	M14x70	-	4150	0,93
414	1"1/4	D404G1/8 L13	32	66,68	95	31,75	78	25	13,5	G1/8 - M10x1	M12x70	1/2"x2"3/4	4150	0,93
414	1"1/4	D404	32	66,68	95	31,75	78	25	15	G1/4 - M12x1,5	M14x70	-	4150	0,92
414	1"1/4	D404 L13	32	66,68	95	31,75	78	25	13,5	G1/4 - M12x1,5	M12x70	1/2"x2"3/4	4150	0,92
414	1"1/2	D405G1/8	38	79,38	112	36,50	94	28	17	G1/8 - M10x1	M16x85	5/8"x3"1/2	4187	1,50
414	1"1/2	D405	38	79,38	112	36,50	94	28	17	G1/4 - M12x1,5	M16x85	5/8"x3"1/2	4187	1,48
414	2"	D406G1/8	51	96,82	134	44,45	114	28	21	G1/8 - M10x1	M20x100	3/4"x4"	4225	2,05
414	2"	D406	51	96,82	134	44,45	114	28	21	G1/4 - M12x1,5	M20x100	3/4"x4"	4225	2,03

DESIGNAZIONE PER ORDINE DESIGNATION FOR ORDER	Materiale / Material	
	S355	AISI 316L
Distanziale con foro metrico Distance piece with metric hole	D...M..	DX...M..
Distanziale con foro gas Distance piece with BSP hole	D...G...	DX...G...

NOTE / NOTES

* Solo in ST52.3
* Only in ST52.3