



Pressione max di esercizio raccomandata Kg/cm ²	Grandezza	Tipo	Dimensioni					Viti	Or tipo
Maximum recommended working pressure Kg/cm ²	Size	Type	Dimensions					Screws	Or type
			B	C	D	H	L	Metric	
SERIE 3000 / 6000									
400	1/2"	CET12C	14	29,7	45	32	8,5	M8x45	4075
400	3/4"	CET34C	19	35,3	50	32	8,5	M8x45	4100
400	1"	CET1C	25	43,8	65	35	11	M10x50	4131
400	1"1/4	CET114C	30	51,6	75	38	13	M12x55	4150
400	1"1/2	CET112C	36	60,0	85	42	15	M14x65	4187
400	2"	CET2C	45	69,4	100	44	17	M16x70	4225
400	2"1/2	CET212C	58	83,4	120	55	21	M20x80	4275
400	3"	CET3C	60	102,5	140	60	21	M20x90	4337
400	4"	CET4C	70	113,2	160	60	25	M24x100	4387

DESIGNAZIONE PER ORDINE DESIGNATION FOR ORDER	Materiale / Material A105 o similare (or similar)
--	--

Solo flangia Only flange	CET...C
-----------------------------	----------------

NOTE / NOTES